

480/482 Legend® Series Digital Weight Indicator



As of: Thursday, February 29, 2024



Standard Features

- LED display (480)
- LCD backlit display (482)
- Time and date, battery backed

Approvals

- Local/remote operation
- Numeric keypad (480 Plus/482 Plus)
- Keyed entries for setpoint values (480 Plus/482 Plus)
- Two independent serial ports
- NEMA Type 4X/IP66 stainless steel washdown enclosure
- Programmable ticket formats for gross, net, accumulator and setpoints
- Five continuous stream formats
- Adapter filter or rolling average filter
- Operator functions through menu for audit trail, preset tare, unit ID, accumulator, time and date, setpoints, communications and print formats
- Eight setpoints, sequenced batch engine
- Configurable with Revolution® software



Measurement
Canada
Approved



WARNING:
Cancer and
Reproductive
Harm California
Proposition 65

Defining Value and Performance

With NEMA Type 4X, stainless steel enclosure and advanced gasket system, the industrial-strength Legend Series is built for dirty, wet environments and demanding workplaces, inside or out. Choose between large, ultra-bright LED or LCD 0.8-inch displays with 6-digits and sharp contrast for superior display visibility.

Advanced circuitry withstands electrical noise, power disturbances and transient spikes that are common to industrial applications. The Legend Series' six-button tactile keypad allows for quick navigation and programming. The Legend Plus Series offers a full numeric keypad.

The Legend Series offers a valuable solution for a variety of applications, from basic weighing to batching. Built-in gross/net modes provide quick flexibility for everyday needs. Also utilize the 480's custom ticket printing to modify gross, net and setpoint tokens for a tailored print format.

480/482 Specifications

Power:

Line voltages: 100 to 240 VAC

Frequency: 50/60 Hz

DC voltages: n/a

Power consumption:

8 W

Excitation Voltage:

5 VDC, 8 × 350 ohm or 16 × 700 ohm load cells

Analog Signal Input Range:

±7mV/V

Analog Signal Sensitivity:

0.1 µV/graduation minimum,

0.5 µV/graduation recommended

A/D Sample Rate:

5, 10, 20, 40 Hz, software selectable

Resolution:

Internal: 523,000 counts

Display: 100,000

System Linearity:

Within 0.01% of full scale

Digital I/O:

Optional 2 or 4 inputs

4 or 8 dry-contact relays

Communication Ports:

Com 1: RS-232 full duplex

Com 2: RS-232 full duplex or 20 mA simplex, continuous

Both ports 1200, 2400, 4800, 9600, 19200, 38400 baud seven or eight data bits, even, odd or no parity

(Optional) Analog Output:

16-bit resolution, voltage output 0-10 VDC, current output 0-20 mA / 4-20 mA

(Optional) Relay Board:

Two opto-isolated, 5 to 24 VDC, active high inputs

Primary keys, pseudo functions, batching functions

(4) 30 VDC, 2 amp dry-contact relays

Annunciators:

Gross, net, center of zero, standstill, lb, kg, tare, preset tare

Display:

480/480 Plus: LED display

0.8 in (20 mm), six-digit, seven-segment

482/482 Plus: LCD backlit display,

transmissive/transflective

0.8 in (20 mm), six-digit, seven-segment

Keys/Buttons:

Flat membrane panel, embossed keys, tactile feel

Temperature Range:

Certified: 14 °F to 104 °F (-10 °C to 40 °C)

Operating: 14 °F to 122 °F (-10 °C to 50 °C)

Rating/Material:

NEMA Type 4X/IP66

Stainless steel

Weight:

6.4 lb (2.9 kg)

Warranty:

Two-year limited

EMC Immunity:

EN 50082 Part 2 IEC EN

61000-4-2, 3, 4, 5, 6, 8, and 11

Approvals:

NTEP 12-123, Class III/IIIL, 10,000d

Measurement Canada AM-5892C

OIML R76/2006-NL1-15.24


EU Test Certificate TC8322

CE Marked

cULus

UKCA

480/482 Dimensions



Dimensions					
A	9.50 in (241 mm)	D	3.65 in (92 mm)	G	6.00 in (152 mm)
B	10.00 in (254 mm)	E	2.75 in (70 mm)	H	3.75 in (95 mm)
C	11.00 in (279 mm)	F	7.00 in (178 mm)		

Parts

Part # Description

480 Legend Series 115 VAC

126564 Indicator, 480 Legend LED Display, 115VAC NEMA 5-15 Plug, Stainless Steel Enclosure

130338 Indicator, 480 Legend LED Display, 115VAC NEMA 5-15 Plug, Stainless Steel Enclosure with Analog Output 0-10VDC, 4-20ma.

480 Legend Series 90 to 264 VAC

126565 Indicator, 480 Legend LED Display, 90-264VAC with Euro Plug, Stainless Steel Enclosure

130339 Indicator, 480 Legend LED Display, 90-264VAC with Euro Plug, Stainless Steel Enclosure, With Analog Output 0-10VDC, 4-20ma

480 Plus Legend Series 115 VAC

164588 Indicator, 480 Plus Legend LED Display, Numeric Keypad, 115VAC NEMA 5-15 Plug Stainless Steel Enclosure

164589 Indicator, 480 Plus Legend LED Display, Numeric Keypad, 115VAC NEMA 5-15 Plug with Analog Output 0-10VDC, 4-20ma. Stainless Steel Enclosure

164590 Indicator, 480 Plus Legend LED Display, Numeric Keypad, 115VAC NEMA 5-15 Plug, Digital I/O and Relay Output. Stainless Steel Enclosure.

480 Plus Legend Series 90 to 264 VAC

164591 Indicator, 480 Plus Legend LED Display, Numeric Keypad, 90-264VAC CEE 7/7 Plug Stainless Steel Enclosure

164592 Indicator, 480 Plus Legend LED Display, Numeric Keypad, 90-264VAC CEE 7/7 Plug with Analog Output 0-10VDC, 4-20ma. Stainless Steel Enclosure

164593 Indicator, 480 Plus Legend LED Display, Numeric Keypad, 90-264VAC CEE 7/7 Plug Digital I/O and Relay Output. Stainless Steel Enclosure.

482 Legend Series 115 VAC

164581 Indicator, 482 Legend LCD Display, 115VAC NEMA 5-15 Plug, Stainless Steel Enclosure

482 Legend Series 90-264 VAC

Part #	Description
--------	-------------

164672	Indicator,482 Legend LCD Display, 90-264VAC CEE 7/7 Plug, Stainless Steel Enclosure
--------	---

482 Plus Legend Series 115 VAC

164584	Indicator,482 Plus Legend LCD Display, Numeric Keypad, 115VAC NEMA 5-15 Plug, Stainless Steel Enclosure
--------	---

482 Plus Legend Series 90-264 VAC

164673	Indicator,482 Plus Legend LCD Display, Numeric Keypad, 90-264VAC 7/7 Plug Stainless Steel Enclosure
--------	---

Options

Part #	Description
131340	Bracket,Mounting Assy for Option Modules in 480 Indicator
131341	Ind OPT, Analog Output 480, 0-10VDC, 4-20Ma
131342	Ind OPT, Relay 480 2 Digital Inputs, 4 Dry contact relays
165379	Cable,480 Flash Update Connects into J14 via RS232.
151100	Ind Opt,A/D Sealing Kit Cover for A/D on 480 Indicator
151099	Panel,Mount Option 480/680 Indicator,Gasketed Non-NEMA Seal.
83564	Overlay,Clear Protective Window with Adhesive Edge, Package of Five Each, IQ+355, 320IS, 420, CW90
119201	LIT,Manual 480 Technical 480 Legend Series Technical Manual
165124	LIT,Manual 482 Technical 482 Legend Series Technical Manual

Primary Replacement Components

131345	Overlay, 480 Keypad 6-key For LED window
159612	Overlay, 480 Plus LED Numeric keypad
131346	Display Board,480 LED 7 Segment
161048	Overlay, 482 keypad 6-key Window for LCD Display
161049	Overlay, 482 Plus LCD Numeric Keypad
153776	Display Board,482 LCD 7 Segment Display With BackLight
131316	Power Supply, Switching 85-265VAC Input, 6VDC Output, 480 indicator

Part #	Description
131318	Board ASSY,CPU 480
131319	Board,A/D ASSY 480

www.ricelake.com | 800-472-6703

An ISO 9001 Registered Company ©2023 Rice Lake Weighing Systems